

WHAT IS CLAIMED IS:

1. An organic EL panel having a substrate and an organic EL laminated body formed on the substrate, said organic EL laminated body being formed by interposing at least one organic layer between a pair of electrodes, said organic EL panel further including a cover for protecting the organic EL laminated body from the outside air, characterized in that:

at least one desiccating member is provided within the cover and separated from the organic EL laminated body; and

a concave portion is formed on one surface of the desiccating member, said one surface being orientated to face the organic EL laminated body.

2. The organic EL panel according to claim 1, wherein the desiccating member is a hygroscopic molded body attached to the inner surface of the cover, the hygroscopic molded body has a concave surface facing the organic EL laminated body.

3. The organic EL panel according to claim 1, wherein the desiccating member is a hygroscopic molded body attached to the inner surface of the cover, the hygroscopic molded body has a plurality of concave portions formed on its one surface facing the organic EL laminated body.

4. The organic EL panel according to claim 2 or 3, wherein the inner surface of the cover is formed with at least one attachment

section adapted to receive the hygroscopic molded body.

5. The organic EL panel according to any one of claims 1 - 4,  
wherein a drop prevention sheet for preventing the drop of desiccating  
5 member is provided between the desiccating member and the organic  
EL laminated body.

6. A method of manufacturing an organic EL panel, including device  
formation step of forming, on a substrate, an organic EL laminated  
10 body including a pair of electrodes and at least one organic layer  
interposed between the pair of electrodes; and encapsulation step  
of bonding a cover to the substrate for protecting the organic EL  
laminated body from the outside air, characterized in that:

at least one desiccating member is introduced into the cover  
15 prior to the encapsulation step; and

a concave portion is formed on one surface of the desiccating  
member, said one surface being orientated to face the organic EL  
laminated body.

20 7. The method according to claim 6, wherein the desiccating member  
is a hygroscopic molded body attached to the inner surface of the  
cover, one surface of the desiccating member facing the organic  
EL laminated body is formed by forming the surface into concave  
shape.

25

8. The method according to claim 6, wherein the desiccating member  
is a hygroscopic molded body attached to the inner surface of the

cover, one surface of the hygroscopic molded body facing the organic EL laminated body is formed by forming a plurality of concave portions thereon.

5 9. The method according to claim 7 or 8, wherein the inner surface of the cover is provided with at least one attachment section, the hygroscopic molded body is attached to the at least one attachment section.

10 10. The method according to any one of claims 6 - 9, wherein a drop prevention sheet for preventing the drop of desiccating member is provided between the desiccating member and the organic EL laminated body.